




# **Dip Switch Setting for A1**











\*If the A1 has low resolution monitor (480 x 234), please set

















1. Use Remover Key to Pull out headunit



2. All you need to disconnect is PINK connector and connect provided Green video connector



## **AUDI 3G MMI / A1 - DASH REMOVAL - #1**



7. All you need to disconnect is Pink connector. And connect provided GREEN video connector from N20A Interface.



8. Remove the marked trim part - it held by clips.




9. The Pink connector from No.7, has to be brought out towards the opened trim area, from No.8



### **AUDI 3G MMI / A1 - DASH REMOVAL - #1**



From No.9 - after trim removed, locate the CAN Gate connector.




12. From the main connector of FP20A Interface, Connect CAN HI / CAN-LOW Wires. Then Reconnect it to the CAN GATE PLUG.



11. The marked harness is the CAN Gate plug. Disconnect it with care.

Once CAN wiring is finished, reassemble the trim.

E D A E R O F T-INTERFACE















#### **Optional Remote Control Setting**




#### While in reverse mode:

- 1. Number '1' will show up on top left corner once press OK button on remote controller.
- 2. Press OK Button 4 more times and will see Number '4' on top left corner.
- 3. Press POWER Button on remote to enter the setting screen. (\* The car must be on reverse mode.)
- 4. Keep go down by pressing ▼ button till find 'Warning language menu. then press ▶ on remote to enter language setting.
- 5. Once all the settings are done, pres 'POWER' button again to save & exit.



Number of inputs will be displayed on top left corner




Pressing Power button on remote will bring up the menu screen.



PDC POSITION

Move to Warning / Language tab.

Then Select ENGLISH



Move to PDC ON /OFF tab

Then turn the PDC Off.

Due to Audi A1 does not have Optical Parking Display -Not needed.